

Portable DVD PLAYER

VXM-2000

Super Slim Size



- * Super Slim Size
(Dimension 178 (W) X 42 (H) X 220 (D) mm)
- * Outstanding Compatibility

Slot-In Loading Mechanism
Operating Temp -5°C ~ 50°C
Storage Temp -25°C ~ 70°C
Any Angle Mounting
Supports MPEG-1, 2 Program Streams
Vacuum Fluorescent Display (VFD)
Anti-Shock Buffer Memory
Last Memory on/ off
Power Source DC 12 V – 24V

Vertical Mounting



SPECIFICATIONS

Compatibility

DVD-Video/DVD-R/DVD-RW/DVD+R/DVD+RW
CD/CD-R/CD-RW
DVD/VCD/SVCD/MP3/ WMA(optional)
8cm / 12cm
NTSC / PAL Disc Playback

DVD Features

DVD-5, DVD-9, DVD-10, DVD-18 readable
Color On Screen Display
OSD Language : English
Multiple aspect ratio support (widescreen, letterbox, PAN & SCAN)
Multi - Angle support
Multi - Subtitle support

Audio Features

Digital Audio Output (coaxial)
24-Bit / 96KHz DAC for Down-Mixed 2 channel
Built-In Dolby Digital Decoder
Built-In DTS Decoder (optional)

Connection

Stereo Audio output
3 Video output (S-Video, Composite x 2)
VGA (optional)
1 Digital Audio output



Accessory (Optional)

IR Remote Controller
Cable for Power supply (DC) : 2M
AV cable (RCA) : 2M
Mounting Brackets
Remote eye sensor : 5M
Cigarette lighter adapter

VXM-2100



VXM-2200



VXM-2300



	VXM-2000	VXM-2100	VXM-2200	VXM-2300
AV Input	O	O	O	O
Analog Audio Out	L / R	L / R	L / R	L / R
Digital Audio Out	Coaxial	Coaxial	Coaxial	Coaxial
Video Out	S-Video, Composite x 2	S-Video, Composite x 2	S-Video, Composite x 2	S-Video, Composite x 2
Rear Panel (optional)	VGA / Component			
	FM Modulator			



DVS Korea Co., Ltd.
5th, 7th & 8th Floor, KPS Bldg. 196 Kungok-dong Boondang-ku, Sungnam City Kyungki-do 463-726, Korea.
Tel : 82-31-710-3800 / Fax 82-31-714-8312 <http://www.dvs.co.kr> / sales@dvs.co.kr

DVS America
1180 Aster Ave. Unit#F Sunnyvale, CA 94086 USA
Tel : 408-260-3301 / Fax : 408-260-3305 <http://www.dvsystems.com> / shaunk@dvsystems.com